

HST-01 Heat Seal Tester

HST-01 Heat Seal Tester seals the specimen to determine the seal parameters of basic film, laminated films, coating paper and other heat sealing laminated films according to the requirement of relative standards. The seal parameters include heat seal temperature, dwell time, and the pressure of heat seal. Heat seal materials that have different melting point, heat stability, fluidness, and thickness of could show various heat seal properties, which cause obviously different seal technique.



CHARACTERISTICS

P.I.D. for precise sealing temperature control

Uniform heating by aluminum encapsulated sealing jaws and no inhomogeneous heating

Multiple groups of test parameters can be saved to reduce setting time and eliminate human error

Independent heating of upper and lower sealing jaws on the model of Heat Seal Tester.

Sealing jaw customization available in term of dimension, shape and surface

TECHNICAL INDEXES

Seal Temperature: room temperature~300°C

Temperature Control Accuracy: $\pm 0.2^{\circ}\text{C}$

Dwell Time: 0.1s~9999s

Dwell Pressure: 0.15MPa~0.7MPa

Seal Surface: 330 mm x 10 mm (Sealing Surface)(Customization Available)

Heat Type: Double heat surface

Gas Source Pressure: 0.5MPa~0.7Mpa (Users prepare gas source themselves)

Gas Source Inlet: $\Phi 6\text{mm}$ polyurethane pipe

Power: AC 220V 50Hz

STANDARDS

ASTM F2029

CONFIGURATION

Standard: Mainframe, footswitch

Please Note: pictures used are for illustration purposes only and may differ from the actual product received.

Shinetime International and Leading Instruments are always dedicated to the innovation and improvement of product performance and function. Therefore, technical specifications are subject to change without further notice.

Shinetime International reserves the rights of final interpretation and revision.