

BST-02 Auto Burst Strength Tester

BST-02 Auto Burst Strength Tester for cardboard is widely used in testing the burst strength of packaging materials such as ordinary paper, corrugated paper, toilet paper, wrapping paper etc. Also it can test the leather, cloth, packaging film etc. And it can effectively inspect the quality of the products.



CHARACTERISTICS

Micro-computer control, LCD display;

Computer control system, open architecture, highly automatic program, to ensure the high accuracy, and convenience to operate.

Automatic measurement, Intelligent calculating functions.

Equipped with micro-printer, convenient to get the test result.

Mechatronics modern design concept, hydraulic system, compact structure, nice appearance, easy maintenance.

Self-developed software, having automatical measure, statistics, print test results, data save function.

Mini-printer;

RS232 port;

TECHNICAL INDEXES

Capacity High Pressure 0~100 Kg/ cm² (0.1kg/cm²)

Units(changeable) Kpa, psi, kg/cm²

Material of the Ring Stainless Steel SUS304

Accuracy $\pm 0.5\%$

Pressure Range 200~6000kpa

Specimen Clamping Force >690kpa

Oil 85% Glycerin; 15% Distilled Water

Outside Dimension(L×W×H) 445×425×525 mm

Sensing method Pressure Converter

motor Anti-vibration Motor 1/8 HP

Opening in Upper Clamp 31.5 ± 0.05 mm Diameter

Opening in Lower Clamp 31.5 ± 0.05 mm Diameter

STANDARDS

ISO2759 ASTM D774

Leading Instruments

Please Note:

Pictures used are for illustration purposes only and may differ from the actual product received.

Shinetime International and Leading Instruments are always dedicated to the innovation and improvement of product performance and function. Therefore, technical specifications are subject to change without further notice.

Shinetime International reserves the rights of final interpretation and revision.